

XP-T58NC

Thermal Receipt Printer

Key features

- Big gear printing head
- Equipped with auto cutter
- Low-noise thermal printing
- Cost effective, Easy operation and maintenance
- Support cash drawer driver, various communication interfaces
- Support simplified/traditional Chinese, Japanese, Korean and many other international languages



POS Printer



Specifications

Model	XP-T58NC
Printing method	Direct thermal
Printing speed	90mm/s
Paper width	57.5 ± 0.5mm
Paper diameter	60mm
Paper thickness	0.06-0.08mm
Column capacity	384 dots/line
Line space	3.75mm (changeable using commands)
Character size	ANK, Font A: 12×24 dots Font B: 9×17 dots simplified/traditional Chinese: 24x24 dots
Bar code	UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) /CODABAR/ITF/CODE39/CODE93/CODE128
Code page	PC347 (Standard Europe) 、Katakana、PC850 (Multilingual) 、PC860 (Portuguese) 、PC863 (Canadian-French) 、PC865 (Nordic) 、West Europe、Greek、Hebrew、East Europe、Iran、WPC1252、PC866 (Cyrillic#2) 、PC852 (Latin2) 、PC858、IranII、Latvian、Arabic、PT151 (1251)
NV FLASH	64K Bytes
Input buffer	32K Bytes
Power supply	DC 12V ≈ 2.6A
Cash drawer control	DC 12V = 1A
Interface	Parallel/Serial/USB/Lan
Auto cutter	Partial
Reliability	Printing head life: 50 km Auto cutter life: 500 thousand cuts
Working environment	Temperature (0-45°C), humidity(10-80%)
Storage environment	Temperature (-10-60°C), humidity(10-90%)
Drivers	Win 9X/Win ME/Win 2000/Win 2003/Win NT/Win XP/Win Vista/Win 7/Win 8/Win 8.1/Linux/Win10
Command	Compatible with ESC/POS
Gross weight	1.05 kg
Dimension	190 × 135 × 125.5mm (D × W × H)